

MODEL YB-80 Series**Features:**

40M (A)50M(B)visible distance; low power consumption and wide- voltage(8-15VDC) technology ; IP 55 weatherproof standard ;sun-shield housing and alumi bracket ; dust-avoid protect glass; 1 lux mini illumination (IR leds on); Tech Info.

Available Models

	Model No	CCD	TV Lines
B/W	YB-80P-A/-B	LG1/3	420TVLines
	YB-80PH-A/-B	SONY1/3	580TVLines
Color	YC-80P-A/-B	SHARP1/4	420TVLines
	YC-80PSQ-A/-B	SONY1/4	420TVLines
	YC-80PQ-A/-B	SONY1/3	420TVLines
	YC-80PH-A/-B	SONY1/3	480TVLines

DIALER Seguridad Electrónica SRL

La Rioja 827 (C1221ACG) Ciudad de Buenos Aires - Argentina | Tel/Fax: (54 11) 4932-3838 | dialerseguridad@dialer.com.ar
www.dialer.com.ar

VIDEO



Weight(g)	1000	Size(mm)	170*100*98
Power consumption	A:MAX450MA B:MAX550MA		
Lens	3.5~8mm(Varifocal)	IR LED Visible Range	A:40M B:50M

General Specifications

		B/W camera	Color camera
TV system		CCIR/EIA	NTSC/PAL
Sync System		Internal	
Mini Illumination		1 Lux 5600 K 0 Lux(IR ON)	
White Balance	Mode	AUTO	
	Range	3200~10000K	
Gain control		Auto	
S/N Ratio		>48dB	
Electronic Shutter		1/50~1/12,000 sec.	
Auto Iris		A.E.S	
Video out		Composite output 1.0V p-p at 75 ohm	
Gamma Correction		0.45	
Working Temp.		-10°C To 50°C	
Power Supply		DC12V±1V	

DIALER Seguridad Electrónica SRL

La Rioja 827 (C1221ACG) Ciudad de Buenos Aires - Argentina | Tel/Fax: (54 11) 4932-3838 | dialerseguridad@dialer.com.ar
www.dialer.com.ar

INCENDIO

VIDEO

ACCESOS

INTRUSION

COMUNICACIONES