MILLIOHM METER

Model: MO-2002 *ISO-9001, CE, IEC1010*









FEATURES

- * 4 terminal devices for accurate measurement of very low resistance.
- * Ideal for measuring the resistance of components precisely.
- * Wide measuring range, 0.01 m ohm 20K ohm, 7 ranges.
- * 20 mm, large size LED display.
- * Built-in over input protection.
- * Durable bench type housing case.
- * Built-in over input protection.

LUTRON ELECTRONIC

Bench type

MI LLI OHM METER

Model: MO-2002

* 4 terminal devices for accurate measurement of very low resistance. * Ideal for measuring the resistance of components precisely. * Ideal for testing protective conductors, lightning conductors and welded points. * Wide measuring range, 0.01 m ohm - 20K ohm, 7 ranges. * 20 mm, large size LED display, easy read-out. * LSI circuit provides high accuracy, reliability and durability. * Built-in over input protection.

* Durable bench type housing plastic case stand.

* Built-in over input protection.

GENERAL SPECIFICATIONS			
Test Range	20 m ohm (1 A DC)		
(Test Current)	200 m ohm (1 A DC)		
	2 ohm (100 mA DC)		
	20 ohm (10 mA DC)		
	200 ohm (1 mA DC)		
	2 K ohm (100 uA DC)		
	20 K ohm (10 uA DC)		
Warning Setup	* Warning LED Indicator		
	* Buzzer		
Operating Temp.	0 to 50 °C (32 to 122 °F).		
Operating Humidity	Less than 80 % R.H		
Power Supply	AC 110V ± 15%, 50/60 Hz		
	or AC 230V ± 15%, 50/60 Hz.		
Fuse for Power	* for Power		
Supply	* Size : 5 X 20 mm dia		
Dimension	ion 280 x 210 x 90 mm		
	(11.0 x 8.3 x 3.5 inch)		
Weight	Approx. 2.2 Kg (4.85 LB).		
Standard	Power Cord 1 PC.		
Accessories	4 wire with 2 Kelvin clips 1 pair.		
	Instruction Manual 1 PC.		

ELECTRICAL SPECIFICATIONS (23 ± 5 °C)					
Range	Resolution	Test current	Accuracy		
20 m ohm	0.01 m ohm	1 A	± (0.2 % + 6 d)		
200 m ohm	0.1 m ohm	1 A			
2 ohm	1 m ohm	100 mA			
20 ohm	0.01 ohm	10 mA	± (0.2% + 4d)		
200 ohm	0.1 ohm	1 mA			
2 K ohm	0.001 K ohm	100 uA			
20 K ohm	0.01 K ohm	10 uA			
@ The above a	accuracy is based on the	e reading value.			
Range	Open Circuit Voltage				
20 m ohm	Approx. DC 4.5 V				
200 m ohm	Approx. DC 4.5 V				
2 ohm	Approx. DC 4.5 V				
20 ohm	Approx. DC 4.1 V				
200 ohm	Approx. DC 3.3 V				
2 K ohm	Approx. DC 2.7 V				
20 K ohm	Approx. DC 1.9 V				

^{*} Appearance and specifications listed in this brochure are subject to change without notice.